

RTS Application Guide

CADILLAC

This fitment guide applies to vehicles with O.E. suspension, wheel wells, and brakes unless otherwise noted.

Other sizes and offsets are available, please call the Sales and Tech Department for more information at 800-788-9353

2009-15 CTS-V Sedan

	Size	Vehicle Location	Weld Offset	Weld B/S	S71 Black Center Part Number	S71 All Polished Part Number	S75 Black Center Part Number	S76 Black Center Part Number	S77 Black Center Part Number
15"	15x10	Rear only		7.5	71MB-510N75C*	71MP-510N75C*		76MB-510N75C*	77MB-510N75C*

* Requires CarlyleRacing 15" Conversion kit 15-209-V2-0915

17"	17x5.0	Front	-21	2.20	71HB7050N22A*	71HP7050N22A*	75HB7050N22A*	76HB7050N22A*	77HB7050N22A*
	17x7.0	Front	5	4.20	71HB7070N42A*	71HP7070N42A*	75HB7070N42A*	76HB7070N42A*	77HB7070N42A*
	17x8.0	Front & Rear	18	5.20	71HB7080N52A*	71HP7080N52A*	75HB7080N52A*	76HB7080N52A*	77HB7080N52A*
	17x9.0	Front & Rear	31	6.20	71HB7090N62A*	71HP7090N62A*	75HB7090N62A*	76HB7090N62A*	77HB7090N62A*
	17x10.0	Rear only	44	7.20	71HB7100N72A	71HP7100N72A	75HB7100N72A	76HB7100N72A	77HB7100N72A
	17x10.5	Rear only	50	7.70	71HB7105N77A~	71HP7105N77A~	75HB7105N77A~	76HB7105N77A~	77HB7105N77A~

* Denotes: Front wheel application requires 3/16" (5mm) spacer & will exceed fender by 3/8" (9mm)

~ This application is for the CTS-V Coupe only

Front/Rear tire heights must be within 1/2" (13mm) of each other to prevent traction control errors

18"	18x5.0	Front	-23	2.10	71HB8050N21A*	71HP8050N21A*	75HB8050N21A*	76HB8050N21A*	77HB8050N21A*
	18x8.0	Front & Rear	15	5.10	71HB8080N51A*	71HP8080N51A*	75HB8080N51A*	76HB8080N51A*	77HB8080N51A*
	18x9.0	Front & Rear	28	6.10	71HB8090N61A*	71HP8090N61A*	75HB8090N61A*	76HB8090N61A*	77HB8090N61A*
	18x10.0	Rear only	41	7.10	71HB8100N71A	71HP8100N71A	75HB8100N71A	76HB8100N71A	77HB8100N71A
	18x10.5	Rear only	47	7.60	71HB8105N76A	71HP8105N76A	75HB8105N76A	76HB8105N76A	77HB8105N76A

* Denotes: Front wheel application will exceed fender by 3/16" (5mm)

Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors

20"	20x7.0	Front	8	4.30	71HB0070N43A*	71HP0070N43A*	75HB0070N43A*	76HB0070N43A*	77HB0070N43A*
	20x8.0	Front & Rear	20	5.30	71HB0080N53A*	71HP0080N53A*	75HB0080N53A*	76HB0080N53A*	77HB0080N53A*
	20x9.0	Front & Rear	31	6.30	71HB0090N63A*	71HP0090N63A*	75HB0090N63A*	76HB0090N63A*	77HB0090N63A*
	20x10.0	Rear only	46	7.30	71HB0100N73A	71HP0100N73A	75HB0100N73A	76HB0100N73A	77HB0100N73A
	20x10.5	Rear only	50	7.70	71HB0105N77A	71HP0105N77A	75HB0105N77A	76HB0105N77A	77HB0105N77A

* Denotes: Front wheel application will exceed fender by 3/16" (5mm)

Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors

2016+ CTS-V/ATS-V

	Size	Vehicle Location	Weld Offset	Weld B/S	S71 Black Center Part Number	S71 All Polished Part Number	S75 Black Center Part Number	S76 Black Center Part Number	S77 Black Center Part Number
15"	15x10	Rear only		7.5	71MB-510N75C*	71MP-510N75C*		76MB-510N75C*	77MB-510N75C*

* Requires CarlyleRacing 15" Conversion kit 15-209-V3-16

2016 ATS-V

	Size	Vehicle Location	Weld Offset	Weld B/S	S71 Black Center Part Number	S71 All Polished Part Number	S75 Black Center Part Number	S76 Black Center Part Number	S77 Black Center Part Number
17"	17x5.0	Front	-21	2.20	71HB7050N22A	71HP7050N22A	75HB7050N22A	76HB7050N22A	77HB7050N22A
	17X7.0	Front	5	4.20	71HB7070N42A	71HP7070N42A	75HB7070N42A	76HB7070N42A	77HB7070N42A
	17X8.0	Front & Rear	18	5.20	71HB7080N52A	71HP7080N52A	75HB7080N52A	76HB7080N52A	77HB7080N52A
	17x9.0	Front & Rear	31	6.20	71HB7090N62A	71HP7090N62A	75HB7090N62A	76HB7090N62A	77HB7090N62A
	17x10.0	Rear only			71HB7100N72A*	71HP7100N72A*	75HB7100N72A*	76HB7100N72A*	77HB7100N72A*

Front/Rear tire heights must be within 1/2" (13mm) of each other to prevent traction control errors

* Denotes: Needs tire clearance verified

18"	18x5.0	Front	-23	2.10	71HB8050N21A	71HP8050N21A	75HB8050N21A	76HB8050N21A	77HB8050N21A
	18x8.0	Front & Rear	15	5.10	71HB8080N51A	71HP8080N51A	75HB8080N51A	76HB8080N51A	77HB8080N51A
	18x9.0	Front & Rear	28	6.10	71HB8090N61A	71HP8090N61A	75HB8090N61A	76HB8090N61A	77HB8090N61A
	18x10.0	Rear only			71HB8100N71A*	71HP8100N71A*	75HB8100N71A*	76HB8100N71A*	77HB8100N71A*

Front/Rear tire heights must be within 1/2" (13mm) of each other to prevent traction control errors

* Denotes: Needs tire clearance verified

20"	20x7.0	Front	8	4.30	71HB0070N43A	71HP0070N43A	75HB0070N43A	76HB0070N43A	77HB0070N43A
	20x8.0	Front & Rear	20	5.30	71HB0080N53A	71HP0080N53A	75HB0080N53A	76HB0080N53A	77HB0080N53A
	20x9.0	Front & Rear	31	6.30	71HB0090N63A	71HP0090N63A	75HB0090N63A	76HB0090N63A	77HB0090N63A
	20x10.0	Rear only			71HB0100N73A*	71HP0100N73A*	75HB0100N73A*	76HB0100N73A*	77HB0100N73A*

Front/Rear tire heights must be within 1/2" (13mm) of each other to prevent traction control errors

* Denotes: Needs tire clearance verified